

## EJH 020 1-Stage Specifications

Frame Size	020										
Stage	1-Stage										
Ratio	Unit	Note	5	6	7	8	9	10	15		
Nominal Output Torque	[Nm]	--	67	73	78	82	84	86	89		
Maximum Acceleration Torque	[Nm]	--	90	99	105	111	113	115	120		
Emergency Stop Torque	[Nm]	--	384	407	429	441	441	441	452		
No Load Running Torque	[Nm]	*1	1.61								
Nominal Input Speed	[rpm]	--	2,000								
Maximum Continuous Input Speed	[rpm]	--	4,000								
Maximum Cyclic Input Speed	[rpm]	--	4,000								
Maximum Radial Load	[N]	*2	6,670								
Maximum Axial Load	[N]	*3	1,820								
Moment of Inertia ( $\leq \varnothing 14$ )	[kgcm <sup>2</sup> ]	--	1.52	1.28	1.14	1.04	0.98	0.94	0.83		
Moment of Inertia ( $\leq \varnothing 19$ )	[kgcm <sup>2</sup> ]	--	1.72	1.48	1.34	1.24	1.18	1.14	1.03		
Moment of Inertia ( $\leq \varnothing 28$ )	[kgcm <sup>2</sup> ]	--	2.89	2.66	2.52	2.42	2.36	2.31	2.21		
Efficiency	[%]	*4	92	91	91	91	90	90	88		
Torsional Rigidity	[Nm/arcmin]	--	17.8								
Maximum Torsional Backlash (Standard)	[Arc-min]	--	$\leq 24$								
Maximum Torsional Backlash (Low)	[Arc-min]	--	$\leq 11$								
Noise Level	[dBA]	*5	$\leq 75$								
Ambient Temperature	[°C]	--	-25 ~ 100								
Permitted Housing Temperature	[°C]	--	100								
Protection Class	--	--	IP65								
Lubrication	--	--	Synthetic Oil								
Service Life	[Hours]	--	25,000								
Weight	[kg]	*6	12								

\*1) Torque at no load applied to the input shaft at 2,000 rpm

\*2) The maximum radial load the gearbox can accept

\*3) The maximum axial load the gearbox can accept

\*4) The efficiency at the nominal output torque rating

\*5) Measured with no load applied to the input shaft at 2,000 rpm

\*6) Weight may vary slightly between models

## EJH 020 1-Stage Specifications

Frame Size	020							
Stage	1-Stage							
Ratio	Unit	Note	20	25	30	40	50	60
Nominal Output Torque	[Nm]	--	89	88	85	81	78	75
Maximum Acceleration Torque	[Nm]	--	116	116	112	106	102	98
Emergency Stop Torque	[Nm]	--	418	418	395	362	305	294
No Load Running Torque	[Nm]	*1	1.61					
Nominal Input Speed	[rpm]	--	2,000					
Maximum Continuous Input Speed	[rpm]	--	4,000					
Maximum Cyclic Input Speed	[rpm]	--	4,000					
Maximum Radial Load	[N]	*2	6,670					
Maximum Axial Load	[N]	*3	1,820					
Moment of Inertia (≤ Ø14)	[kgcm <sup>2</sup> ]	--	0.79	0.77	0.76	0.75	0.75	0.75
Moment of Inertia (≤ Ø19)	[kgcm <sup>2</sup> ]	--	0.99	0.97	0.96	0.95	0.95	0.95
Moment of Inertia (≤ Ø28)	[kgcm <sup>2</sup> ]	--	2.17	2.15	2.14	2.13	2.13	2.13
Efficiency	[%]	*4	85	84	80	76	73	70
Torsional Rigidity	[Nm/arcmin]	--	17.8					
Maximum Torsional Backlash (Standard)	[Arc-min]	--	≤ 24					
Maximum Torsional Backlash (Low)	[Arc-min]	--	≤ 11					
Noise Level	[dBA]	*5	≤ 75					
Ambient Temperature	[°C]	--	-25 ~ 100					
Permitted Housing Temperature	[°C]	--	100					
Protection Class	--	--	IP65					
Lubrication	--	--	Synthetic Oil					
Service Life	[Hours]	--	25,000					
Weight	[kg]	*6	12					

\*1) Torque at no load applied to the input shaft at 2,000 rpm

\*2) The maximum radial load the gearbox can accept

\*3) The maximum axial load the gearbox can accept

\*4) The efficiency at the nominal output torque rating

\*5) Measured with no load applied to the input shaft at 2,000 rpm

\*6) Weight may vary slightly between models