

VRS SERIES Inline Planetary

VRS 075 1-Stage Specifications

Frame Size	075											
Stage	1-Stage											
Ratio	Unit	Note	3	4	5	6	7	8	9	10		
Nominal Output Torque	[Nm]	*1	50	75	75	75	75	75	50	50		
Maximum Acceleration Torque	[Nm]	*2	80	125	125	125	125	125	80	80		
Emergency Stop Torque	[Nm]	*3	200	250	250	250	250	250	200	200		
Nominal Input Speed	[rpm]	*4	3000									
Maximum Input Speed	[rpm]	*5	6000									
No Load Running Torque	[Nm]	*6	0.35									
Permitted Radial Load	[N]	*7	2300	2500	2700	2800	3000	3100	3200	3300		
Permitted Axial Load	[N]	*8	3400	3700	3900	3900	3900	3900	3900	3900		
Maximum Radial Load	[N]	*9	4300									
Maximum Axial Load	[N]	*10	3900									
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	--	--	--	--	--	--	--	--		
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.670	0.470	0.380	0.340	0.310	0.300	0.290	0.290		
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	1.100	0.930	0.850	0.810	0.780	0.760	0.750	0.750		
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	3.100	2.900	2.900	2.800	2.800	2.800	2.800	2.800		
Efficiency	[%]	*11	95									
Torsional Rigidity	[Nm/arc-min]	*12	10									
Maximum Torsional Backlash	[arc-min]	--	≤ 3									
Noise Level	dB [A]	*13	≤ 67									
Protection Class	--	*14	IP54 (IP65)									
Ambient Temperature	[°C]	--	0-40									
Permitted Housing Temperature	[°C]	--	90									
Weight	[kg]	*15	3.4									

VRS 075 2-Stage Specifications

Frame Size	075											
Stage	2-Stage											
Ratio	Unit	Note	15	16	20	25	28	30	35	40		
Nominal Output Torque	[Nm]	*1	50	75	75	75	75	50	75	75		
Maximum Acceleration Torque	[Nm]	*2	80	125	125	125	125	80	125	125		
Emergency Stop Torque	[Nm]	*3	200	250	250	250	250	200	250	250		
Nominal Input Speed	[rpm]	*4	3000									
Maximum Input Speed	[rpm]	*5	6000									
No Load Running Torque	[Nm]	*6	0.06									
Permitted Radial Load	[N]	*7	3700	3800	4000	4300	4300	4300	4300	4300		
Permitted Axial Load	[N]	*8	3900	3900	3900	3900	3900	3900	3900	3900		
Maximum Radial Load	[N]	*9	4300									
Maximum Axial Load	[N]	*10	3900									
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.130	0.140	0.130	0.120	0.140	0.099	0.120	0.098		
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.280	0.300	0.280	0.280	0.290	0.250	0.270	0.250		
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	0.720	0.730	0.720	0.710	0.730	0.700	0.710	0.690		
Moment of Inertia ($\leq \emptyset 28$)	[kgcm ²]	--	--	--	--	--	--	--	--	--		
Efficiency	[%]	*11	90									
Torsional Rigidity	[Nm/arc-min]	*12	10									
Maximum Torsional Backlash	[arc-min]	--	≤ 3									
Noise Level	dB [A]	*13	≤ 67									
Protection Class	--	*14	IP54 (IP65)									
Ambient Temperature	[°C]	--	0-40									
Permitted Housing Temperature	[°C]	--	90									
Weight	[kg]	*15	3.8									

VRS 075 2-Stage Specifications

Frame Size	075										
Stage	2-Stage										
Ratio	Unit	Note	45	50	60	70	80	90	100		
Nominal Output Torque	[Nm]	*1	50	75	75	75	75	50	50		
Maximum Acceleration Torque	[Nm]	*2	80	125	125	125	125	80	80		
Emergency Stop Torque	[Nm]	*3	200	250	250	250	250	200	200		
Nominal Input Speed	[rpm]	*4	3000								
Maximum Input Speed	[rpm]	*5	6000								
No Load Running Torque	[Nm]	*6	0.06								
Permitted Radial Load	[N]	*7	4300	4300	4300	4300	4300	4300	4300		
Permitted Axial Load	[N]	*8	3900	3900	3900	3900	3900	3900	3900		
Maximum Radial Load	[N]	*9	4300								
Maximum Axial Load	[N]	*10	3900								
Moment of Inertia ($\leq \varnothing 8$)	[kgcm ²]	--	0.120	0.098	0.098	0.097	0.097	0.097	0.097		
Moment of Inertia ($\leq \varnothing 14$)	[kgcm ²]	--	0.270	0.250	0.250	0.250	0.250	0.250	0.250		
Moment of Inertia ($\leq \varnothing 19$)	[kgcm ²]	--	0.710	0.690	0.690	0.690	0.690	0.690	0.690		
Moment of Inertia ($\leq \varnothing 28$)	[kgcm ²]	--	--	--	--	--	--	--	--		
Efficiency	[%]	*11	90								
Torsional Rigidity	[Nm/arc-min]	*12	10								
Maximum Torsional Backlash	[arc-min]	--	≤ 3								
Noise Level	dB [A]	*13	≤ 67								
Protection Class	--	*14	IP54 (IP65)								
Ambient Temperature	[°C]	--	0-40								
Permitted Housing Temperature	[°C]	--	90								
Weight	[kg]	*15	3.8								

- *1) At nominal input speed, service life is 20,000 hours
- *2) The maximum torque when starting or stopping operation
- *3) The maximum torque allowed under a stress situation (Permitted 1,000 times during service life)
- *4) The average input speed
- *5) The maximum intermittent input speed
- *6) Torque at no load applied to the input shaft at nominal input speed
- *7) At this load and nominal input speed, service life will be 20,000 hours. (The radial load applied to the output side shaft center)
- *8) At this load and nominal input speed, service life will be 20,000 hours. (The axial load applied to the output side bearing)
- *9) The maximum radial load that the gearbox can accept
- *10) The maximum axial load that the gearbox can accept
- *11) The efficiency at the nominal output torque rating
- *12) This does not include lost motion
- *13) Contact NIDEC-SHIMPO for the testing conditions and environment
- *14) IP65 (wash-down) is available as an option. Contact NIDEC-SHIMPO for more details
- *15) The weight may vary slightly between models