

EVS SERIES Right-angle Planetary

EVS o6o 2-Stage Specifications

Frame Size	060									
Ratio	Unit	Note	3	4	5	6	7	8	9	10
Nominal Output Torque	[Nm]	*1	12	16	22	24	24	24	19	19
Maximum Acceleration Torque	[Nm]	*2	29	38	48	54	54	54	38	38
Maximum Torque	[Nm]	*3	33	45	56	63	63	61	45	45
Emergency Stop Torque	[Nm]	*4	50	65	80	90	90	90	65	65
Nominal Input Speed	[rpm]	*5				3300				
Maximum Input Speed	[rpm]	*6				6000				
No Load Running Torque	[Nm]	*7				0.33				
Maximum Radial Load	[N]	*8				3000				
Maximum Axial Load	[N]	*9				2700				
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.320	0.271	0.251	0.242	0.235	0.232	0.229	0.228
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.395	0.346	0.326	0.317	0.310	0.307	0.304	0.303
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	0.584	0.535	0.516	0.506	0.500	0.496	0.494	0.492
Efficiency	[%]	*10				93				
Torsional Rigidity	[Nm/arc-min]	*11				3				
Maximum Torsional Backlash	[arc-min]	--				≤ 4				
Noise Level	dB [A]	*12				≤ 80				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				2.0				

EVS o6o 3-Stage Specifications

Frame Size	060									
Ratio	Unit	Note	15	16	20	25	28	30	35	40
Nominal Output Torque	[Nm]	*1	18	26	26	28	28	19	28	28
Maximum Acceleration Torque	[Nm]	*2	38	54	54	54	54	38	54	54
Maximum Torque	[Nm]	*3	38	54	54	54	54	38	54	54
Emergency Stop Torque	[Nm]	*4	65	90	90	90	90	65	90	90
Nominal Input Speed	[rpm]	*5				3800				
Maximum Input Speed	[rpm]	*6				6000				
No Load Running Torque	[Nm]	*7				0.20				
Maximum Radial Load	[N]	*8				3000				
Maximum Axial Load	[N]	*9				2700				
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.074	0.079	0.072	0.071	0.077	0.062	0.070	0.061
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.118	0.124	0.116	0.115	0.122	0.106	0.115	0.106
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	--	--	--	--	--	--	--	--
Efficiency	[%]	*10				88				
Torsional Rigidity	[Nm/arc-min]	*11				3				
Maximum Torsional Backlash	[arc-min]	--				≤ 7				
Noise Level	dB [A]	*12				≤ 80				
Protection Class	--	*13				IP54 (IP65)				
Ambient Temperature	[°C]	--				0-40				
Permitted Housing Temperature	[°C]	--				90				
Weight	[kg]	*14				1.8				

EVS o60 3-Stage Specifications

Frame Size	060								
Ratio	Unit	Note	45	50	60	70	80	90	100
Nominal Output Torque	[Nm]	*1	19	28	28	28	28	19	19
Maximum Acceleration Torque	[Nm]	*2	38	54	54	54	54	38	38
Maximum Torque	[Nm]	*3	38	54	54	54	54	38	38
Emergency Stop Torque	[Nm]	*4	65	90	90	90	90	65	65
Nominal Input Speed	[rpm]	*5			3800				
Maximum Input Speed	[rpm]	*6			6000				
No Load Running Torque	[Nm]	*7			0.2				
Maximum Radial Load	[N]	*8			3000				
Maximum Axial Load	[N]	*9			2700				
Moment of Inertia ($\leq \emptyset 8$)	[kgcm ²]	--	0.070	0.061	0.061	0.061	0.061	0.061	0.061
Moment of Inertia ($\leq \emptyset 14$)	[kgcm ²]	--	0.115	0.106	0.106	0.106	0.105	0.105	0.105
Moment of Inertia ($\leq \emptyset 19$)	[kgcm ²]	--	--	--	--	--	--	--	--
Efficiency	[%]	*10			88				
Torsional Rigidity	[Nm/arc-min]	*11			3				
Maximum Torsional Backlash	[arc-min]	--			≤ 7				
Noise Level	dB [A]	*12			≤ 80				
Protection Class	--	*13			IP54 (IP65)				
Ambient Temperature	[°C]	--			0-40				
Permitted Housing Temperature	[°C]	--			90				
Weight	[kg]	*14			1.8				

*1) At nominal input speed, service life is 20,000 hours

*2) The maximum torque when starting or stopping operation. Apply Cycle Factor f_0 , found on page 468, for higher duty cycle applications

*3) Permitted 10,000 times during service life. Based on 10% of maximum radial load and smooth output shaft

*4) The maximum torque allowed under a stress situation. Permitted 1,000 times during service life

*5) The average input speed at nominal input torque. Maintain housing temperature below permitted value

*6) The maximum intermittent input speed

*7) Torque at no load applied to the input shaft at nominal input speed

*8) The maximum radial load that the gearbox can accept

*9) The maximum axial load that the gearbox can accept

*10) The efficiency at the nominal output torque rating

*11) This does not include lost motion

*12) Contact NIDEC-SHIMPO for the testing conditions and environment

*13) Various wash-down options are available. Contact NIDEC-SHIMPO for more details

*14) Weight may vary slightly between models